

OT-200

Professional Wireless Microphone System



SPECIFICATION

※ 본 기술서는 제품의 성능 향상을 위하여 사전 통보 없이 변경 될 수 있습니다.

RECIVER			
Power Supply Mode	Built-in lithium battery	Communication Method /	
Power Supply	DC 24V/ 3A	Frequency Band	Bluetooth, 2.4G
Charging Current	≤ 1.5A	Sensitivity(pink noise)	> 81dBSPL
Max Power	150W	Effective Working Distance	1.TMIC Tx : 15M / 2.Handheld Tx, Bodypack Tx : 20M
Working Current	< 160 mA	Antenna Connection Mode	Internally installed
Operation Time	≥ 6H	Max SPL	> 90dB
System Delay (Microphone)	< 14mS	6.35mm Input Port	≤ -25dBV
S / N	> 76dB	Pairing Mode	Manual pairing
Distortion	< 0.2%	Dimension(L×W×H),	268×187×205mm,
Frequency Response	140Hz~15kHz	Weight	2380g (Excluding TMIC transmitter)
HAND MIC, BELT PACK		T Mic	
Power Supply Mode	AA Battery×2	Power Supply Mode	Built-in lithium battery(100 mAh)
Frequency Band	2.4G	Operation Time	>4H
S / N	≥ 88dBA	Transmit Power (wired)	9dBm
Frequency Response	120Hz~12kHz (± 2 db)	Distortion	< 0.05% 1kHz
Tx Power Consumption	< 70mA	Frequency Response	120Hz~12kHz (± 2 db)
Tx Transmit Power (wired)	13dBm	Tx Power Consumption	< 25mA
Distortion	< 0.05% 1kHz	Frequency Band	2.4GHz
Working Distance	20M)	S / N	≥ 88dBA
Gain	12dB (Hand Mic), 8dB (Belt Mic)	Gain	8dB
Dimension	Hand Mic : 240×48mm, Belt Mic : 64×190×26 mm (Include antenna)	Working Distance	15M
Weight	Hand Mic : 200g (Exculde battery), Belt Mic : 90g (Exculde battery)	Dimension	33×35×15 mm
		Weight	12g